Corey Pendant

GENERATION LIGHTING

PENDANT

GENERAL PRODUCT INFORMATION:

These fixtures are intended to be installed utilizing NEC compliant junction boxes.

This product is safety listed for damp locations.

Incandescent version may be dimmed with a standard incandescent dimmer. LED version may be dimmed with a LED dimmer. Consult lamp manufacturer for additional information.


This instruction shows a typical installation.

SAVE THESE INSTRUCTIONS!

CAUTION - RISK OF FIRE


This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.

Use minimum 90°C supply conductors.



GENERATION LIGHTING 7400 Linder Ave., Skokie, IL 60077 T 847.410.4400 | F 847.410.4500 www.generationlighting.com

Install the Fixture



- Determine the wanted height or look of the fixture with the provided hang straight (or link and loop) and stems, then assemble by screwing them together. NOTE: Use hang straight for standard ceilings and use link and loop for sloped ceilings.
- 2 Feed the fixture wires through the stem/hang straight assembly and screw it onto the top of the fixture nipple.
- 3 Unscrew the collar nut off the screw collar and place it onto the stem/chain followed by the canopy.
- 4 If necessary, screw the threaded nipple tightly onto the mounting plate.
- 5 Feed the fixture wires through the threaded nipple and screw the mounting plate assembly onto the hang straight or link and loop.
- 6 Align and secure the mounting plate to the junction box.
- 7 Connect the fixture to a suitable ground in accordance to local electrical codes.
- 8 Connect the white fixture wire (square and/or rigid) to the neutral power line wire with a wire nut.
- 9 Connect the black fixture wire (round and/or smooth) to the hot power line wire with a wire nut.
- Neatly place all the wires into the junction box, place the canopy onto the threaded nipple, and secure it in place by screwing the collar nut tightly into the screw collar.
- Screw the lamp into the socket. Refer to the label on the socket for Max Wattage Information.
- 12 Install the lower shade to the upper shade by using the cap nuts and cap screws as shown.